


HFB008



Type 品名	Material 材質	Surface Treatment 表面處理	Delivery 交貨日
HFB008-A	SS400 低碳鋼	Blackening 染黑	7 Working Days 7 個工作日
HFB008-B		Nickel Electroless 鍍無電解鎳	
HFB008-C	SUS304 不鏽鋼	-	
HFB008-D	A6061 鋁合金	Anodizing 白色陽極	
HFB008-E		Black Anodizing 黑色陽極	

ID. TOL. 內徑公差	
D	H7
8~10	+0.015 0
12~16	+0.018 0
20~30	+0.021 0
35~50	+0.025 0

Choose The Type of Flanged 選擇法蘭類型	I	II	III (D8~D10)	III (D12~50)


Type	D	支撐部 厚度(N)	D1	D2	L	L2	T	M	P	K	W	P1	F	d1
HFB008-A HFB008-B HFB008-C HFB008-D HFB008-E	*8	3.5	15	32	16	10	5	M3	25	25	15	25	-	3.5
	8A	3.5	15	32	16	10	5	M4	25	25	15	25	-	4.5
	*10	5	20	38	20	12	5	M3	30	30	20	30	-	4.5
	*12	5	22	40	24	15	6	M4	32	32	25	28	16	4.5
	13	5.5	24	42	26	16	6	M4	34	34	27	28	18	4.5
	15	5.5	26	48	30	18	6	M4	38	38	29	32	18	5.5
	*16	6	28	50	32	19	6	M4	40	39	32	33	22	5.5
	*20	7.5	35	63	32	20	8	M5	50	48	40	42	25	6.6
	*25	7.5	40	68	38	23	8	M5	55	53	45	45	30	6.6
	*30	7.5	45	73	38	24	10	M6	60	58	50	48	35	6.6
	35	10	55	89	50	30	10	M6	72	70	61	58	42	9
	40	15	70	104	50	30	12	M8	87	80	76	68	54	9
	50	15	80	114	50	30	12	M8	97	90	86	73	64	9

※ D/E Type Only Applied For Dimension
Marked *

※ D/E型表面處理僅適用於D尺寸有*符號者

Order Ex. 訂購範例

HFB008-□-8-□



A B C D or E
ID.
I II or III

選擇材質和表面處理方式
內徑尺寸
選擇法蘭類型