


Type 品名	Material 材質	Surface Treatment 表面處理	Delivery 交貨日
HFP046-A	1015 低碳鋼	-	5 Working Days 5 個工作日
HFP046-B		Blackening 染黑	
HFP046-C		Nickel Electroless 鍍無電解鎳	
HFP046-D	SUS304 不鏽鋼	-	

L(mm)	TOL公差 (mm)
<300	±0.2
<600	±0.3
<800	±0.4

Type	H	L(u:0.5mm)	L1(u:1mm)	L2(u:1mm)	M&N	D1	D2	L3	L5
HFP046-A	8	15~250	2~4	2~4	3/4	6	6	1	9.2
	10	15~350	2~5	2~5	4/5	8	8	1	11.5
	12	20~400	2~6	2~6	5/6	10	10	1	13.9
	13	20~400	2~6	2~6	5/6	10	10	1.5	15
	14	25~500	2~8	2~8	6/8	12	12	1	16.2
HFP046-B	17	25~500	2~8	2~8	6/8	12	12	2	19.6
HFP046-C	19	40~500	2~10	2~10	6/8/10/12	16	16	1.5	21.9
HFP046-D	24	50~600	2~12	2~12	6/8/10/12/16	20	20	2	27.7
	27	50~600	2~16	2~16	6/8/10/12/16	24	24	1.5	31.2
	27	50~600	2~16	2~16	6/8/10/12/16	20	20	3.5	31.2
	30	50~600	2~16	2~16	6/8/10/12/16/20	28	28	1	34.6
	30	50~600	2~16	2~16	6/8/10/12/16/20	24	24	3	34.6
	32	50~600	2~20	2~20	6/8/10/12/16/20	30	30	1	36.9
	32	50~600	2~20	2~20	6/8/10/12/16/20	24	24	4	36.9

Order Ex. 訂購範例

HFP046-□-8-L-L1-L2-M-N



A B C or D
Opposite Length of Hexagonal Post
Length of Hexagonal Post
Length of Stepped
Length of Stepped
Choose M (Thread)
Choose N (Thread)

選擇六角柱材質
六角柱對邊長度
六角柱長度
六角柱長度
嵌入部長度
嵌入部長度
選擇螺紋M
選擇螺紋N

Alterations	追加加工名稱	Description	加工說明	Order Ex. 訂購範例
A		Length tolerance change 長度公差變更		HFP046-A-8-100-2-2-M3-N3-A(±0.03) Length tolerance change to ±0.03 長度公差變更為±0.03