


Type 品名	Material 材質	Surface Treatment 表面處理	Delivery 交貨日
HFP040-A	1015 低碳鋼	Blackening 染黑	5 Working Days 5 個工作日
HFP040-B		Nickel Electroless 鍍無電解鍍	
HFP040-C	SUS304 不鏽鋼	-	

L(mm)	TOL 公差 (mm)
< 300	±0.2
< 600	±0.3
< 800	±0.4

Type	H	L	L2	M
HFP040-A	6	15/20/25/30/35/40/45/50	6.9	3
	7	20/25/30/35/40/45/50/60/70/80/90/100/110/120/130/140/150	8.1	4
	8	20/25/30/35/40/45/50/60/70/80/90/100/110/120/130/140/150/200	9.2	5
HFP040-B	10	25/30/35/40/45/50/60/70/80/90/100/110/120/130/140/150/200	11.5	6
HFP040-C	12	25/30/35/40/45/50/60/70/80/90/100/110/120/130/140/150/200	13.9	6
	13	30/35/40/45/50/60/70/80/90/100/110/120/130/140/150/200	15	8
	14	35/40/45/50/60/70/80/90/100/110/120/130/140/150/200	16.2	8
	17	40/45/50/60/70/80/90/100/110/120/130/140/150/200	19.6	10
	19	50/60/70/80/90/100/110/120/130/140/150/200	21.9	12

Order Ex. 訂購範例

HFP040-□-6-L



選擇六角柱材質
六角柱對邊長度
六角柱長度

Alterations	追加加工名稱	Description	加工說明	Order Ex. 訂購範例
A		Length tolerance change 長度公差變更		HFP040-A-6-20-A(±0.03) Length tolerance change to ±0.03 長度公差變更為±0.03